

Tailored Anodization Leads to the Formation of Long, High-Aspect-Ratio TiO₂ Nanotube Arrays for Dye-Sensitized Solar Cells

As dye-sensitized solar cells (DSCs) continue to receive significant attention for their potential as low-cost alternatives to crystalline silicon photovoltaics, it appears that arrays of nanotubular TiO₂ may hold the key to their performance. In particular, the use of long, smooth TiO₂ nanotube arrays instead of disordered nanoparticulate TiO₂ can enhance DSC efficiencies by absorbing larger amounts of photosensitizing dye, leading to increased photoelectron generation. Now, work reported in the September issue of the *Journal of the American Ceramic Society* (DOI: 10.1111/j.1551-2916.2008.02546.x; p. 3086) by Y. Yang, X. Wang, and L. Li at Tsinghua University in Beijing demonstrates that careful control of the conditions of anodization can lead to the formation of smooth TiO₂ nanotube arrays as long as 22 μm, with aspect ratios up to 200.

The researchers began the nanotube formation process by potentiostatically anodizing 99.5%-pure titanium foils in a dimethylformamide electrolyte solution containing 0.5 wt% hydrofluoric acid, under an applied voltage of 30 V. This

resulted in arrays of TiO₂ nanotubes whose length increased with anodization time, saturating at 22 μm after 40 h, which the researchers identify as the point at which the oxide growth and dissolution rates equalize. The nanotubes' wall smoothness also increased with anodization time, and their aspect ratio was as high as 200, as revealed in field-emission scanning electron microscope images. The researchers next created samples using 50 h of anodization time and different (fixed) applied voltages, finding that the average nanotube diameter increased from 110 nm at 20 V to 130 nm at 30 V. A key observation of these experiments was that the nanotubes were covered by a thick protective oxide layer during the anodization, enabling the long growth.

In order to investigate the effectiveness of these long nanotube arrays in solar cells, the researchers first calcined them at 400°C for 3 h and then used them as photoanodes in DSC devices. Although the devices employed an inexpensive and less-effective dye (Indoline dye D102) than the state of the art, the device's conversion efficiency was as high as 3.4%. In light of these results, long, high-aspect-ratio TiO₂ nanotube arrays may bring the

commercial viability of DSCs one step closer to reality.

COLIN MCCORMICK

Morphology and Optical Response of Butterfly Wing Replicated as an Inorganic Glass

The objective of biomimetics is to take advantage of structures found in nature, which have been optimized over millions of years of evolution, for the design of new materials and devices. Biomimetics researchers have been attracted to structures found in insects because they display characteristics that simultaneously serve several functions. For example, the structure of butterfly wings, in addition to making flight possible, is generally responsible for the great diversity of colors and patterns that exist. In one approach to fabricating replicas of biological structures, actual biological samples serve as templates that are coated with inorganic materials such that the microstructure and nanostructure are captured. Butterfly wings are covered with scales to a density of 200–600 scales/mm² arranged in a roof-tile pattern. The replicated scale patterns are complex in structure with stratification, voids, and complex groove shapes that can result in a photonic bandgap structure. A biomimetic

SMART

SCIENCE, MATHEMATICS
& RESEARCH FOR
TRANSFORMATION

PART OF THE NATIONAL DEFENSE
EDUCATION PROGRAM

SMART Scholarship

Science, Mathematics & Research for Transformation



SMART

THE PREMIER SCHOLARSHIP PROGRAM
SUPPORTING THE EDUCATION OF AMERICA'S
FUTURE SCIENTISTS AND ENGINEERS.

The Department of Defense is proud to offer
scholarships and post-graduation career opportunities
to our nation's research leaders of tomorrow.

WWW.ASEE.ORG/SMART

SMART SCHOLARS RECEIVE

- » Generous Cash Award
- » Health Insurance
- » Summer Internships (multi-year participants)
- » Full Tuition and Fees
- » Book Allowance
- » Career Opportunities

SMART SCHOLARS ARE

- » Outstanding students with demonstrated ability and special aptitude in Science, Technology, Engineering & Mathematics (STEM) fields
- » Undergraduate, graduate, and doctoral students
- » Employed, post-degree, as a civilian employee of one of the many DoD research facilities (length of employment is commensurate with length of scholarship funding)
- » Enrolled, accepted, or seeking acceptance at a U.S. college or university (applicants for undergraduate awards must be enrolled)
- » At least 18 years of age and are United States citizens

FOR MORE INFORMATION AND TO APPLY

www.asee.org/smart

QUESTIONS?

Contact: smart@asee.org

technique, called conformal-evaporated-film-by-rotation (CEFR), recently developed by R.J. Martín-Palma, C.G. Pantano, and A. Lakhtakia of The Pennsylvania State University, involves thermally evaporating an inorganic glass onto a rotating biological sample, to replicate at the micro- and nanoscale the morphology of a butterfly wing.

As reported recently in *Applied Physics Letters* (DOI: 10.1063/1.2973167), the researchers replicated a wing of the butterfly *Battus philenor* with chalcogenide glass ($\text{Ge}_{28}\text{Sb}_{12}\text{Se}_{60}$), chosen because of its large index of refraction at visible and infrared (IR) wavelengths, and its high transmittance in the IR. In addition, illumination of chalcogenide glasses can modify the optical bandgap and index of refraction, making them suitable for passive and active infrared devices. The researchers thermally evaporated the chalcogenide glass using a current of 95 A for 30 min, directing the vapor flux toward the substrate at an angle of 85° to normal, with the substrate rotating at a constant speed of 0.5 rotations/s, resulting in a coating about $0.5\ \mu\text{m}$ thick. Scanning electron microscope images show that the replicated structure is composed of thousands of scales with typical dimensions of about $50\ \mu\text{m}$ by $200\ \mu\text{m}$, arranged in rows. A grid of raised longitudinal, quasiparallel lamellae runs the

length of a typical scale, spaced at about $2.5\ \mu\text{m}$. Filling the space between adjacent lamellae is a netlike reticulum, composed of fine tubes. The researchers said that both the lamellae and the reticulum are the optical elements that give the wing its particular color. The researchers used energy dispersive x-ray spectroscopy to show that they fabricated a high-fidelity, chalcogenide glass replica of the original biotemplate without disturbing the original structure. In addition, specular and scattered reflectance spectra in the visible and IR ($200\ \text{nm}$ – $2\ \mu\text{m}$) are similar for the original specimen and the replica; the minor differences were explained by the researchers as due to the difference in the indices of refraction of the wing material and the glass. In addition, the researchers said, "Since the morphology of the butterfly wing makes it a very efficient diffuser of light, the replica could be used as an antireflection structure for increased photon trapping and optical diffusers," and "the CEFR technique might be useful for the development of high-efficiency biomimetic optical devices."

STEVEN TROHALAKI

Higher Order Stop Gaps Observed in Photosensitive Chalcogenide Glasses 3D Photonic Crystals

Photonic crystals (PCs) are key components for the next generation of miniatur-

ized photonic devices because of their capability to control and manipulate the flow of light on a wavelength scale. E. Nicoletti and co-workers from the Swinburne University of Technology, Victoria, and D. Bulla and co-workers from the Australian National University, Canberra, have reported in a recent issue of *Optics Letters* (posted online on September 8) on the observation of first- and second-order stop gaps in the near-infrared wavelength region on three-dimensional (3D) PCs based on photosensitive chalcogenide glasses (ChGs) fabricated by direct-laser-writing.

The researchers used ~ 16 – $20\text{-}\mu\text{m}$ -thick As_2S_3 films deposited on glass slide substrates by thermal evaporation of As_2S_3 bulk glass in a vacuum chamber at 2×10^{-7} Torr and 310°C . Such films contain disconnected molecular cage-like structures (e.g., As_4S_4 , As_4S_6) that can "open" when thermally or optically excited. The researchers produced this effect using a femtosecond Ti:sapphire laser beam (wavelength $800\ \text{nm}$, repetition rate $1\ \text{kHz}$), tightly focused into the films, leading to re-bonding and polymerization of the glass network in highly localized areas of the glass through a two-photon-induced nonlinear process. Subsequently, the researchers dissolved the unpolymerized glass in a solution of diisopentylamine and dimethylsulfoxide in multiple steps, starting with a highly concentrated

Advertisers in This Issue

	Page No.		Page No.
*A & N Corporation	1066	*Janis Research Company, Inc.	991
*Agilent Technologies	1001	*JEOL USA Inc.	1026
*Aldrich/Sigma-Aldrich	1046	*Kurt J. Lesker Company	1035
*Angstrom Sciences	993	*Lake Shore Cryotronics, Inc.	1068
*Annealsys	992	*Leica Microsystems Inc.	1060
*Asylum Research	986	*MDC Vacuum Products, LLC	1052
*Bruker AXS Inc.	1016	*MMR Technologies, Inc.	992
*Carl Zeiss SMT Inc.	1036	NanoScale Science at UNC Charlotte	1074
*CrystalMaker Software Ltd.	1058	National Electrostatics Corp.	1000
*Digital Surf SARL	991	*NT-MDT Co.	1069
*Gatan, Inc.	1015	*Park Systems, Inc.	Inside back cover
*Goodfellow Corporation	1051	Radcliffe Fellowships	997
High Voltage Engineering Europa B.V.	Inside front cover	*Royal Society of Chemistry	1067
*Huntington Mechanical Laboratories, Inc.	Outside back cover	SMART Scholarship/ASEE	989
*Hysitron, Inc.	994	*Veeco Instruments Inc.	985
*International Centre for Diffraction Data (ICDD)	1002	Visitec of America	1059

For the direct link to advertisers in this issue, access www.mrs.org/bulletin_ads.

*Please visit us at the Exhibit, December 2–4, during the 2008 MRS Fall Meeting in Boston.